

Domus Ergo-line Soft

18254 The central idea behind the Domus relax chair is to offer optimal seating comfort in peace and quiet.

The Ergo-line mechanism makes sure that the backrest, seat and legrest simultaneously tilt into a “zero gravity” position.

Support

- The rounded sides consist of 2 OSB boards of 18 mm, and are firmly connected with a metal structure.
- The sides are upholstered with fire-retardant foam.
- The upholstery is finished with imitation leather and decorative stitching.
- Comfortable wide armrests of ± 10 cm.
- All edges and corners have been rounded.
- No visible fastening elements.
- Solid beech legs, equipped with synthetic glides.

Seat

- Removable seat in melaminated MDF, thickness: 12 mm.
- The rounded seat in front stimulates a fluent blood circulation.
- Comfortable seat height of 45 cm.
- Upholstered with fire-retardant foam. Two different density zones guarantee optimal seating comfort.
- The upholstery is finished with imitation leather and decorative stitching.

Backrest and legrest

- The backrest consists of an ergonomic pre-shaped plywood shell, thickness 12 mm.
- Upholstered with fire-retardant foam. This foam has 3 different density zones to guarantee optimal seating comfort.
- The upholstery is finished with imitation leather and decorative stitching.
- Equipped with an adjustable and removable head/neck cushion.
- Legrest: plywood, thickness 10 mm. Upholstered with fire-retardant foam and finished with imitation leather.

Ergo-line mechanism:

- Makes sure that the backrest, seat and legrest simultaneously tilt into a *zero gravity* position (*) by means of a lever that is situated on the right inside of the chair.
- The angle between the seat and backrest ranges from 97° (seating position) to 120° (*'zero gravity'* position).
- When the relax mechanism is activated, the seat inclines to a 24 degree angle.
- A gas spring minimizes the necessary activation strength of the mechanism.
- Thanks to a lever that is situated on the right inside of the chair, it is possible to lock the chair in every position.
- When the chair is put in the seat position, the legrest will be turned inwards so that you can stand up without any problem.

Colours

We would like to refer to our extensive colour gamut.
Sample card + samples available on request.


(*) Zero gravity position: this seat/lying position is based on NASA data. A neutral body position converts all muscle power into a biomedical balance. (Source: "From outer space to you", Omni, March 1994.)



Dimension

18254 | Domus Ergo-line Soft:

- W 76 x D 79 x H 115 cm
- Seat height: 45 cm
- Seat depth: 51 cm
- Seat width: 52 cm
- Height armrests: 66 cm
- Safe working load: 135 kg



Materials and finishing

- Wood: Solid beech, Plywood, OSB, MDF.
- Metal: epoxy coating (light grey).
- Fire-retardant foam.
- Upholstery: see collection.
- Resistant to the common cleaning products.

For further information about used **materials, constructions and maintenance**: consult our materialfiles.

Options

- Cushion with visco-elastic foam and a bi-elastic cover.
- Anatomical reduction cushion.
- Lateral headrest.
- Bracket for fixation straps.
- Case for IV rod.
- IV rod.
- Hidden twin castors, $\varnothing 32$ mm in front, $\varnothing 50$ mm at the back with brakes and a brake bracket.
- Design castors $\varnothing 100$ mm with brake.
- Design castors $\varnothing 100$ mm with brake and 2 directional castors.
- Footrest (only with castors $\varnothing 100$ mm).
- Removable headrest.

